

Fibre Optic Patch Leads

Fibre Optic Connectors (Manual)

Product Code: FOPLCON

Feature

- Comply with : JIS C-5973, IEC, Bellcore
- High stable mating and de-mating characteristics
- Optimum optical performance through high quality ferrule
- Designed for variable cable diameter
- Available long flange for ferrule and Angled ferrule
- Widely used for LD/PD modules



Specifications

Characteristics	Values
Structure	Satisfied Telcordia GR-326-CORE
Fibre Type	SM(9/125), MM(50/125, 62.5/125)
Insertion Loss	≤ 0.2dB (against master connector)
Mating durability	≤ 0.2dB (500 times)
Operating temperature stability	≤ 0.3dB (-40°C ~ +85°C)

Ordering Information

OFC - - - - - - - - X - X X - X X X

Type	Ferrule Type	Ferrule Inner Dia. (μm)	Ferrule Cap colour	Boot Colour	Boot Dia (MM)	X Configuration	XX Housing Colour	XXX Width of key
SC FC ST LC MU MTRJ E-2000 Biconic	N: Without ferrule P: PC ferrule PL: PC ferrule with long flange S: Step APC ferrule C: Cone APC ferrule AL: Angled ferrule with long flange	250: 125(SM) 255: 125.5(SM) 260: 126(SM,MM) 270: 127(MM)	B: Blue K: Black G: Green Y: Yellow	B: Blue K: Black G: Green Y: Yellow R: Red W: White O: Option	09: 0.9 16: 1.6 20: 2.0 24: 2.4 30: 3.0	P: One-piece pre assembled K: Multipiece *Only SC Type	B: Blue G: Green GR: Gray Only SC,LC Type	N: 2.09mm - 2.14mm R: 1.97 – 2.02mm *Only FC type

Minimum order quantity: 5 pieces of any type